




39 BEACON STREET BOSTON, MA


























































# #39 BEACON STREET BENJAMIN MOORE CLASSIC PAINT COLORS




FRONT DOOR ESSEX GREEN PM-11



WINDOWS & IRON WORK BLACK PM-9

White Dove

FRONT ENTRY TRIM WHITE DOVE PM-19



**Siedle Steel - Video Door station - Intercom Unit** Recess mounted with **3** push buttons (One shown)



## Flush Mount FDC Inlet-

#### Flush Mount FDC Inlet

Designed to provide supplemental water to a building's fire protection system. These units feature a body that's typically concealed behind a wall with only the plate, snoots, and plugs exposed.

250 GPM per inlet

U/L Listed and FM Approved (2-way only)

- 2-way standard equipment: Units are equipped with a brass clappered concealed FDC body, wall plate, 2½" F NPT x 2½" F swivel NST snoots, and 2½" plugs.
- 3-way, 4-way, and 6-way standard equipment: Units are equipped with a 6061
   -T6 aluminum concealed FDC body, wall plate, 3" F NPT x 2½" F swivel NST clappered snoots, and 2½" plugs.




120PBSA


Part #	Туре	Size & Configuration	Outlet Type	Outlet Location	A	В	С
120	2-Way	4" x 2½" x 2½"	Female NPT	Back	111/4"	6"	7"
121	2-Way	4" x 2½" x 2½"	Female NPT	Bottom	111⁄4"	6"	7"
122	2-Way	4" x 2%" x 2%"	Female NPT	Тор	111/4"	6"	7"
123	2-Way	4" x 2½" x 2½"	Groove	Back	111/4"	6½"	7°
124	2-Way	4" x 2½" x 2½"	Groove	Bottom	11½"	6"	7"
125	2-Way	4" x 2½" x 2½"	Groove	Тор	111/4"	6"	7"
126	2-Way	6" x 2½" x 2½"	Female NPT	Back	11¼"	7½"	7 5/8"
127	2-Way	6" x 2½" x 2½"	Female NPT	Bottom	111/4"	91/2"	7 5/8"
128	2-Way	6" x 2½" x 2½"	Female NPT	Тор	111/4"	9½"	7 5/8"
130	3-Way	6" x 2½" x 2½" x 2½"	Groove	End	193/4"	81/2"	7"
131	3-Way	6" x 2%" x 2%" x 2%"	Groove	Back	19%"	10%"	7"
132	3-Way	6" x 2½" x 2½" x 2½"	Groove	Top / Bottom	19¾"	8½"	7"
133	3-Way	6" x 2W" x 2W" x 2W"	Female NPT	End	19%"	8½"	7"
134	3-Way	6" x 2½" x 2½" x 2½"	Female NPT	Back	19¾"	10½"	7"
135	3-Way	6" x 2%" x 2%" x 2%"	Female NPT	Top / Bottom	19%"	81/2"	7"
140	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	End	26¾"	81/2"	7"
141	4-VVay	6" x 2½" x 2½" x 2½" x 2½"	Groove	Back	26%"	10%"	7"
142	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Groove	Top / Bottom	26¾"	81/2"	7"
143	4-VVay	6" x 2%" x 2%" x 2%" x 2%"	Female NPT	End	26%"	8%"	7"
144	4-Way	6" x 2½" x 2½" x 2½" x 2½"	Female NPT	Back	26¾"	10½"	7"
145	4-Way	6" x 2%" x 2%" x 2%" x 2%"	Female NPT	Top / Bottom	26%"	8%"	7"
150	4-Way	6" x 21/2" x 21/2" x 21/2" x 21/2" (Square)	Groove	Top / Bottom	141⁄4"	8"	- 7"
151	4-Way	6" x 2½" x 2½" x 2½" x 2½" (Square)	Groove	Back	14%"	10%"	7"
160	6-Way	6" x 2½" x 2½" x 2½" x 2½" x 2½" x 2½"	Groove	End	40¾"	81/2"	7"
161	6-Way	8' x 2%' x 2%' x 2%' x 2%' x 2%' x 2%'	Groove	End	40%"	9%"	7"


Specify Finish:	Specify Wall Plate Lettering:	Specify Orientation:		
RB Rough Brass	-A Auto Spkr	-Horizontal (standard)		
-PB Polished Brass	Standpipe	V Vertical		
PC Polished Chrome	-SA Standpipe & Auto Spkr	· .		
	DS Dry Standpipe			



# Flush Mount FDC Inlet-







Search Catalog

Browse Catalog

Contact Us

Home



#### Product Information

Item No.: 667 1/2" Sq. Spear

Dimensions: Height: 4.5 in. Width: 2.25 in.

Weight: 0.45 lb.


<< Back to Search




### LiveRoof LITE SYSTEM

Over Conventional Roofing Assembly


### SIDE VIEW





LiveRoof System Saturated Weight: 15-17 lbs / sf

ILLUSTRATIONS ARE TO CONCEPTUALLY ASSIST PROFESSIONALS IN DESIGNING LIVEROOF INSTALLATIONS, LIVEROOF DOES NOT ACCEPT RESPONSIBILTY FOR ENGINEERING BASED ON ILLUSTRATIONS. A QUALIFIED ROOFING SPECIALIST SHOULD BE CONSULTED TO DETERMINE APPROPRIATE WATERPROOFING AND ROOF DECK MATERIALS AND SUITABLE DESIGN.



NOT TO SCALE

LITE A v2012-01-18

liveRoof