









 \bigcirc

JR972	Technical Dat	a Sneet
Double Coated UPVC Tape		
Description: JR972 Is a double coated white, UPVC tape with an acrylic solvent based adhesive that offers	Nominal Values: The following data are nominal values based on PSTC, ASTM and other industry standard test. The data should no be considered as exact specifications.	
evel which provides quick bonding strength.	Carrier:	UPVC film
ever which provides quick bonding strength.	Adhesive:	Acrylic
Designed for Interior and Exterior Bonding Applications.	Adhesion to Steel: (oz/inch of width) PSTC-1	88 oz/inch
	Tensile Strength: (lbs/inch of width) PSTC-31	15.4 lbs/inch
	Elongation: (at break)	150%
Product Applications:	Thickness: (mil) PSTC-33	8.3 mil
 Banner Hems Mounting of Nameplates, Trophies, Labels and Signs 	Temperature Range: Operating - °F	-22°F~194°F
 Wood and Decorative Trim such as PVC Profiles for the Furniture Industry License Plate Frames 	Color:	White
Features and Benefits:		2
 Excellent Plasticizer Migration Resistance Quick stick and Easy Tear or Punch Good Resistance to Solvents, Chemicals, UV and Heat Affixes Decorative Trim such as PVC Profiles 	Part	D
nnotec of Wisconsin, Inc. 1220 Mound Ave Suite #140	Phone: 1-800-776-7194 WI: 262-637-7103	
Racine, WI 53404	Fax: 262-637-8205	
WWW.innotape.com While we believe them to be reliable, the statements and information herein are only for gene	sales@innotape.com	